

IP Solution

SV-NHD10SDI

2.0MP Speed Dome Camera



- IP 56 Dust & Water proof
- 10X Optical Zoom
- 3 Groups Guard Tours
- 40 Meters IR Distance
- Ambient Light Detection
- 1080P Full HD
- ONVIF 2.2 / OSD Menu
- Park Action (Scan, Tour)
- Lighting Protection
- PWM (IR Optic)

Specifications

Model	SV-NHD10SDI
Image Sensor	1/2.7" Progressive Scan CMOS
Resolution	Effective 1920(H)x1080(V) / Stream 1280(H)x720(V)
Focal Length	5.1mm ~ 51mm
Angle of View	H : 52°(W) ~ 5.8°(T) , V:39°(W) ~ 4°(T)
Protocol	TCP/IP, HTTP, FTP, RTSP, UPnP, DNS, NTP, RTP, UDP, IGMP
Web Application	IE, CMS, Management Platform
Mobile View	Windows, Symbian, iphone platform
Preset	128 Points
IR LED Control	PWM (Intelligent IR dependant the zoom ratio)
ICR, Min Illumination	Manual, Auto (0.1 Lux ICR off, 0.01 Lux ICR on)
IR distance	40 Meters
PT Speed, Range	Pan 15°/s, Tilt 30°/s, 360° Continuous, 94° (Auto Flip 180° / 90°)
Manual PT Speed	0.01 ~ 50°/s - 0.01~30°/s
Go To Preset Speed	50°/s
Guard Tours, Points	3 Groups, Max 16 Points each group (Dwell Time Set)
PWR on Action	Memory / Pattern 1 / Tour 1 / 360° Scan / A-B Scan / Preset
PoE Built-In	Optional
Ambient Light Detection	1 ~ 15 Grades Selectable
Operating Temperature	0°C ~ +40°C
Humidity	95% Non Condensing
Lighting Protection	Transient Voltage 3000V
Power Source	DC 12V (1A)
Size / Weight	4.5" / 1.2 KG (N.W)

Dimension Unit : mm

